

Balancing the wheels of transportation

Application Chart Per Tire

## For Light and Medium Trucks

TIRE SIZE	1/2 TON	1 TON+	TIRE SIZE	1/2 TON	1 TON+	TIRE SIZE	1/2 TON	1 TON+	TIRE SIZE	1/2 TON	1 TON+
LIGHT TRUCK				-				and the second second		and a second	and a second
	14"		265/70R16	3 oz.	4 oz.	255/55R17	3 oz.	4 oz.	355/60R20	5 oz.	6 oz.
215/75R14	3 oz.	4 oz.	275/70R16	3 oz	4 oz.	275/55R17	3 oz.	5 oz.	275/55R20	3 oz.	4 oz
205/70R14	3 oz.	4 oz.	305/70R16	3 oz.	4 oz.	345/55R17	3 oz.	5 oz.	285/55R20	3 oz.	4.0Z
215/70R14	3 oz.	4 oz.	315/70R16	4 oz	6 oz.	255/50R17	3 oz.	4 oz.	255/50R20	3 oz.	4 0Z
1999-1999-1999-1999-1999-1999-1999-199	15"		355/70R16	5 oz.	6 oz.	COLOR STATE AND IN	17.5"		285/50R20	3 oz.	4 oz.
700R15		4 oz	365/70R16	5 oz.	6 oz.	8R17.5	5 oz.	5 oz.	305/50R20	4 oz.	6 oz
7.50R15		6 oz.	395/70R16	5 oz.	6 oz.	8.5R17.5	6 oz.	6 oz.	325/50R20	4 oz.	6 oz
8.25R15		6 oz.	195/65R16	3 oz.	4 02.	9R17.5	6 oz.	6 oz.	355/50R20	4.oz.	6 oz.
9R15		8 oz.	215/65R16	3 oz.	4.0Z.	9.5R17.5	8 oz.	8 oz.	325/45R20	4 oz.	6 oz.
10R15		8 oz.	225/65R16	3 oz.	4 oz.	10R17.5	8 oz.	8 oz.	275/40R20	4 oz.	6 oz.
215/80R15	3 oz.	4 oz	245/65R16	3 oz.	4 oz.	11R17.5	8 oz.	8 oz.	315/35R20	4 oz.	6 oz.
195/75R15	3 oz.	4 oz.	255/65R16	3 oz.	4 OZ.	225/90R17.5	8 oz.	8 oz.	and the second second	22"	
205/75R15	3 oz.	4 oz.	305/65R16	3 oz.	4 oz.	205/80R17.5	8 oz.	8 oz.	325/55R22	5 oz.	6 oz.
215/75R15	3 oz.	4 oz.	345/65R16	5 oz.	6 oz.	225/80R17.5	8 oz.	8 oz.	335/55R22	5 oz.	6 oz.
225/75R15	4 oz.	4 oz.	375/65R16	5 oz.	6 oz.	205/75R17.5	6 oz.	6 oz.	325/50R22	4 oz.	6 oz.
235/75R15	4 oz.	4 0Z	215/60R16	3 oz.	4.0Z.	215/75R17.5	6 oz.	6 oz.	305/45R22	4 oz.	6 oz.
245/75R15	3 oz.	4 oz.	225/60R16	3 oz.	4 oz.	225/75R17.5	6 oz.	6 oz.	305/40R22	4 oz.	6 oz.
255/75R15	3 oz.	4 oz.	235/60R16	3 oz.	4 oz.	235/75R17.5	6 oz.	6 oz.	285/35R22	3 oz.	5 oz.
265/75R15	3 oz.	4 oz.	285/60R16	3 oz.	4 oz.	245/75R17.5	6 oz.	6 oz.	0051457004	24"	
235/70R15	3 oz.	4 oz.	255/55R16	3 oz.	4 oz.	195/70R17.5	6 oz.	6 oz.	325/45R24	4 oz.	6 oz.
245/70R15	3 oz.	4 oz.	315/55R16	3 oz	4 oz.	215/70R17.5	6 oz.	6 oz.			
255/70R15	3 oz.	4 oz.	345/55R16	3 oz.	5 oz.	235/70R17.5	6 oz.	6 oz.			
265/70R15	4 oz.	4 02	355/55R16	3 oz.	5 oz.	195/60R17.5	6 oz.	6 oz.			
285/70R15	4 oz.	4 0Z	375/55R16	4 0Z	6 oz.	205/60R17.5	6 oz.	6 oz.	(M) Impro	ve Fuel E	conomy
315/70R15	4 oz.	5 oz.	245/50R16	3 oz.	4 oz.	225/60R17.5	6 oz.	6 oz.		100000000000000000000000000000000000000	and the second sec
245/65R15	3 oz.	4 0Z	0040.5	16.5"		7.50040	18"	0			
225/60R15	3 oz.	4 oz.	8R16.5 8.75R16.5	5 oz.	5 oz.	7.50R18 255/70R18	8 oz.	8 oz.			
325/60R15	4 oz 15.5"	5 oz.	9.50R16.5	6 oz.	6 oz. 6 oz.	265/70R18	3 oz.	5 oz.	Incres	ase Tire L	ife
185/70R15.5	3 oz.	4 oz	10R16.5	6 oz. 6 oz.	6 oz.	275/70R18	3 oz.	6 oz.			-110
100/101(10.5	16"	A UZ	12R16.5	8 oz.	8 oz.	275/65R18	4 oz.	6 oz.			
6.50R16	10	4 oz.	121(10.5	17"	0.02.	285/65R18	4 oz.	6 oz.			
7.50R16		4 oz	235/80R17	6 oz.	6 oz.	325/65R18	4 oz.	6 oz.		1.111	
8.25R16	-	6 oz.	235/75R17	6 oz.	6 oz.	355/65R18	4 oz.	6 oz.	( Reduc	ce Mainte	nance
11R16	-	8 oz.	245/75R17	6 oz.	6 oz.	395/65R18	6 oz.	8 oz.			
215/85R16	3 oz.	4 oz.	255/75R17	6 oz.	6.0Z.	245/60R18	3 oz.	4 oz.			
225/85R16	3 oz.	4 02	285/75R17	6 oz.	8 oz.	255/60R18	3 oz.	5 oz.			
235/85R16	3 oz.	4 az	245/70R17	4 oz.	6 oz.	265/60R18	3 oz.	5 oz.	Redu	ce Vibrati	on
245/85R16	3 oz.	4 oz.	255/70R17	4 oz.	6 oz.	275/60R18	4 oz.	6 oz.			ion -
255/85R16	4 oz.	5 oz.	265/70R17	6 oz.	6 oz.	285/60R18	4 02.	6 oz.			
265/85R16	4 oz.	5 oz.	275/70R17	6 oz.	6 oz.	325/60R18	4 oz.	6 oz.			
275/85R16	4 oz.	5 oz.	285/70R17	6 oz.	6 oz.	375/60R18	6 oz.	8 oz.			1.225
205/80R16	3 oz.	4 oz.	305/70R17	6 oz.	8 oz.	395/60R18	6 oz.	8 oz.	🛛 💋 ) Enviro	onmental	y Friendly
325/80R16	4 oz	6 oz.	315/70R17	6 oz.	8 oz.	255/55R18	3 oz.	4 oz.		and the second second second	And the second se
175/75R16	3 oz.	4 oz.	355/70R17	6 oz.	8 oz.	275/55R18	3 oz.	4 02			
195/75R16	3 oz.	4 oz.	225/65R17	3 oz.	4 oz.	285/55R18	3 oz.	4 oz.		Chiles.	
225/75R16	3 oz.	4 oz	235/65R17	3 oz.	4 oz.	285/50R18	3 oz.	4 oz.	Troub	le Free	
235/75R16	3 oz.	4 oz	245/65R17	3 oz.	4 oz.	375/50R18	4.02	6 oz.			
245/75R16	3 oz.	4 oz.	255/65R17	3 oz.	5 oz.		19"				
265/75R16	4 oz	6 oz.	265/65R17	4 oz	6.oz.	255/55R19	3 oz.	4 oz.	Counteract	Balancin	g Beads
285/75R16	4 oz.	6 oz.	305/65R17	4 oz.	6 oz.	255/50R19	3 oz.	4 oz.	are not rec		
295/75R16	4 oz	6 oz.	375/65R17	6 oz.	8 oz.	275/45R19	3 oz.	4 oz.			
315/75R16	4 oz.	6 oz.	225/60R17	3 oz.	4 oz.	285/45R19	3 oz.	4 0Z		enger ca	
215/70R16	3 oz.	4 oz.	235/60R17	3 oz.	4 oz.	STREET, STREET, STREET, ST	20"	C 10	For motorc		
225/70R16	3 oz	4 oz.	255/60R17	4 oz.	6 oz.	325/75R20	6 oz.	8 oz.	please se	e our ch	nart at
235/70R16	3 oz	4 oz	275/60R17	4 oz.	6 oz.	275/65R20	4.02.	6 oz.	www.bik		
245/70R16	3 oz	4 oz.	285/60R17	4 oz	6 oz.	275/60R20	4 oz	6 oz.		ebeaus.	Com
255/70R16	3 oz	4 oz.	225/55R17	3 oz.	4 oz.	325/60R20	4 oz.	6 oz.			





DUAL

8 oz 8 oz

8 oz 8 oz 10 oz 10 oz 10 oz 12 oz 14 oz

10 oz 10 oz 12 oz 12 oz 14 oz 14 oz 14 oz 14 oz 14 oz 16 oz 16 oz 16 oz

10 oz. 10 oz. 12 oz. 14 oz.

			Balancing th	e wheels of ho
TIRE SIZE	SINGLE	DUAL	TIRE SIZE	SINGLE
OFF BOAD	2			17"
OFF-ROAD	14"		22/42 50047	
27/8 50014			33/12.50R17	6 oz.
27/8.50R14	3 oz.		35/12.50R17	6 oz.
00/0 50045	15"		37/12.50R17	8 oz.
29/9.50R15	4.oz.		37/13.50R17	10 oz.
30/9.50R15	4 oz		40/13.50R17	10 oz.
33/9.50R15	6 oz.		05/40 50040	18"
31/10.50R15	4 oz.		35/12.50R18	6 oz.
33/10.50R15	6 oz.		37/12.50R18	8 oz.
31/11.50R15	4 oz.		05/40 50000	20"
32/11.50R15	6 oz.		35/12.50R20	6 oz.
31/12.50R15	5 oz.		37/12.50R20	8 oz.
32/12.50R15	6 oz.		MED. TRUCK	
33/12.50R15	6 oz.			19.5"
35/12.50R15	6 oz.	1	8R19.5	6 oz.
36/12.50R15	8 oz.		9R19.5	6 oz.
37/12.50R15	8 oz.		18R19.5	14 oz.
35/13.50R15	8 oz.		280/75R19.5	8 oz.
31/14.50R15	6 oz.		285/75R19.5	8 oz.
33/14.50R15	8 oz.		225/70R19.5	6 oz.
36/14.50R15	10 oz.		245/70R19.5	6 oz.
38/15.50R15	10 oz.		265/70R19.5	8 oz.
33/16.50R15	8 oz.		275/70R19.5	8 oz.
36/16.50R15	10 oz.		285/70R19.5	8 oz.
40/17B15	10 oz.		305/70R19.5	10 oz.
44/18.50B15	12 oz.		385/65R19.5	12 oz.
	16"		445/65R19.5	14 oz.
32/9.50R16	6 oz.		4	20"
35/10.50R16	6 oz.		7.50R20	8 oz.
31/12.50R16	6 oz.		8.25R20	8 oz.
32/12.50R16	6 oz.		9.00R20	10 oz.
33/12.50R16	6 oz.		10.00R20	10 oz.
34/12.50R16	6 oz.	1	11.00R20	12 oz.
35/12.50R16	6 oz.		12.00R20	12 oz.
36/12.50R16	8 oz.		12.5R20	12 oz.
37/12.50R16	8 oz.		13/80R20	12 oz.
33/14.50R16	8 oz.		14/80R20	12 oz.
36/14.50R16	10 oz.	_	14.00R20	16 oz.
38/15.50R16	10 oz.	1	365/80R20	16 oz.
	16.5"		395/80R20	16 oz
31/10.50R16.5	4 oz.			20.5"
33/12.50R16.5	6 oz.		525/65R20.5	20 oz.
35/12.50R16.5	6 oz.		615/65R20.5	22 oz.
37/12.50R16.5	8 oz.			22"
33/14.50R16.5	8 oz.		10.00R22	12 oz.
35/14.50R16.5	8 oz.		11.00R22	12 oz.
38/15.50R16.5	10 oz.		and the second sec	22.5"
33/16.50R16.5	8 oz.		9R22.5	8 oz.
36/16.50R16.5	10 oz.		10R22.5	8 oz.
40/17B16.5	10 oz.		11R22.5	10 oz.
44/18.50B16.5	12 oz.	<u> </u>	12R22.5	12 oz.

TIRE SIZE	SINGLE	DUAL
13R22.5	12 oz.	-
15R22.5	12 oz.	
16R22.5	14 oz.	-
16.5R22.5	14 oz.	-
18R22.5	16 oz.	-
235/80R22.5	6 oz.	8 oz.
255/80R22.5	8 oz.	10 oz.
275/80R22.5	10 oz	12 oz.
295/80R22.5	12 oz.	14 oz.
315/80R22.5	14 oz.	
365/80R22.5	14 oz.	
245/75R22.5	8 oz.	10 oz.
265/75R22.5	8 oz.	10 oz.
285/75R22.5	10 oz.	12 oz.
295/75R22.5	10 oz.	12 oz.
315/75R22.5	12 oz.	Alex Mark
345/75R22.5	12 oz.	
350/75R22.5	14 oz.	
235/70R22.5	6 oz.	8 oz.
255/70R22.5	8 oz.	10 oz.
11/70R22.5	8 oz.	10 oz.
265/70R22.5	8 oz.	10 oz.
275/70R22.5	10 oz	12 oz.
305/70R22.5	10 oz.	12 oz.
315/70R22.5	10 oz.	12 oz.
365/70R22.5	12 oz.	TE OL.
365/65R22.5	12 oz.	-
385/65R22.5	12 oz.	
425/65R22.5	14 oz.	
445/65R22.5	16 oz.	
285/60R22.5	10 oz	
295/60R22.5	10 oz.	
305/60R22.5	10 oz.	
315/60R22.5	10 oz.	
385/55R22.5	12 oz.	-
455/55R22.5	16 oz.	
275/50R22.5	10 oz.	12 oz.
445/50R22.5	16 oz.	12 02
110/00/122.0	24"	
11.00R24	14 oz.	71
12.00R24	14 oz.	
14.00R24	16 oz.	
445/70R24	16 oz.	
495/70R24	16 oz.	
TO OT OTALT.	24.5"	
11R24.5	10 oz.	12 oz.
12R24.5	14 oz.	14 oz.
285/75R24.5	10 oz.	12 oz.
305/75R24.5	10 oz.	12 oz.
315/75R24.5	10 oz.	12 oz.
275/80R24.5	10 oz.	12 oz.
295/80R24.5	10 oz.	12 oz.

To achieve maximum results it is important to use the proper package size for each tire. As a rule of thumb, the amount of Counteract required per tire is based on one ounce per thirteen pounds of tire. If you are using our throw in bags, open & discard outside bag only & throw clear inner bag containing Counteract directly inside tire cavity. If you are not using an applicator and pouring the contents of the bag directly into the tire it is imperative that none of the contents of the bag ends up on the bead seating area of the tire and rim. Counteract disclaims any responsibility for air loss or tire damage due to improper installation or air check. In order to reduce the possibility of valve leaks, the use of a Counteract valve core and a metal CBB valve cap is recommended and included in every bag of Counteract. Counteract is TPMS compatible.

